

PLATE HEAT EXCHANGER TECHNICAL SPECIFICATION

CUSTOMER	Výměníky Ostrava	DATE	27-II-2016
PROJECT		ITEM	Stibor Miroslav ing.
PHE MODEL	A4S-P10-111-H L=1000 AISI 316L 0.4 EPDM HT		
REV NO		HOT SIDE	COLD SIDE
HEAT EXCHANGED	kW	1 000,00	
MASS FLOWRATE	kg/s	23,81	23,84
VOLUMETRIC FLOWRATE	m ³ /h	85,89	85,98
INLET TEMPERATURE	°C	90,00	75,00
OUTLET TEMPERATURE	°C	80,00	85,00
PRESSURE DROP	bar	0,50	0,50
FLUID PROPERTIES			
MEDIUM		Water	Water
DENSITY	kg/m ³	966,06	968,98
SPECIFIC HEAT	kJ/(kg.°C)	4,20	4,20
THERMAL CONDUCTIVITY	W/(m.°C)	0,67	0,66
VISCOSITY - MEAN	mPa.s	0,33	0,36
VISCOSITY - WALL	mPa.s	0,36	0,36
FOULING FACTORS	(m ² .°C)/kW	0,01	0,01
OVERSURFACE FACTOR		10,22	
INLET PORT		F1	F3
OUTLET PORT		F4	F2
DESIGN AND MECHANICAL SPECIFICATION			
HOT SIDE FLOW ARRANGEMENT		55 × 1 + 0 × 0	
COLD SIDE FLOW ARRANGEMENT		55 × 1 + 0 × 0	
TOTAL NUMBER OF PLATES		111	
CHANNEL MIXING (NUMBER/TYP)		110 H	
EFFECTIVE HEAT TRANSFER AREA	m ²	26,16	
CLEAN U-VALUE	W/(m ² .°C)	8 515,92	
SERVICE U-VALUE	W/(m ² .°C)	7 645,26	
LMTD	°C	5,00	
PLATE THICKNESS / MATERIAL		0.40 mm AISI 316L	
GASKET MATERIAL / TYPE		EPDM HT	
DESIGN TEMPERATURE	°C	120,00	
WORKING PRESSURE	bar	10,00	
TEST PRESSURE	bar	13,00	
DESIGN CODE		PED 97/32/EC	
LIQUID VOLUME	L	65,40	
MAX. NUMBER OF PLATES		144	
NET WEIGHT	kg	491,99	
FLOODED WEIGHT	kg	557,39	
CONNECTION HOT		DN100 Flange St.37 PN10	
CONNECTION COLD		DN100 Flange St.37 PN10	