

PLATE HEAT EXCHANGER TECHNICAL SPECIFICATION

| | | | |
|--|---|----------------------------|----------------------|
| CUSTOMER | Výměníky Ostrava | DATE | 27-II-2016 |
| PROJECT | | ITEM | Stibor Miroslav ing. |
| PHE MODEL | A2M-P10-101-HM28 L=1000 AISI 316L 0.4 EPDM HT | | |
| REV NO | | HOT SIDE | COLD SIDE |
| HEAT EXCHANGED | kW | 500,00 | |
| MASS FLOWRATE | kg/s | 11,91 | 11,92 |
| VOLUMETRIC FLOWRATE | m ³ /h | 42,95 | 42,99 |
| INLET TEMPERATURE | °C | 90,00 | 75,00 |
| OUTLET TEMPERATURE | °C | 80,00 | 85,00 |
| PRESSURE DROP | bar | 0,39 | 0,39 |
| FLUID PROPERTIES | | | |
| MEDIUM | | Water | Water |
| DENSITY | kg/m ³ | 966,06 | 968,98 |
| SPECIFIC HEAT | kJ/(kg.°C) | 4,20 | 4,20 |
| THERMAL CONDUCTIVITY | W/(m.°C) | 0,67 | 0,66 |
| VISCOSITY - MEAN | mPa.s | 0,33 | 0,36 |
| VISCOSITY - WALL | mPa.s | 0,36 | 0,36 |
| FOULING FACTORS | (m ² .°C)/kW | 0,00 | 0,00 |
| OVERSURFACE FACTOR | | 0,70 | |
| INLET PORT | | F1 | F3 |
| OUTLET PORT | | F4 | F2 |
| DESIGN AND MECHANICAL SPECIFICATION | | | |
| HOT SIDE FLOW ARRANGEMENT | | 50 × 1 + 0 × 0 | |
| COLD SIDE FLOW ARRANGEMENT | | 50 × 1 + 0 × 0 | |
| TOTAL NUMBER OF PLATES | | 101 | |
| CHANNEL MIXING (NUMBER/TYPER) | | 72 H × 28 M | |
| EFFECTIVE HEAT TRANSFER AREA | m ² | 14,85 | |
| CLEAN U-VALUE | W/(m ² .°C) | 6 781,15 | |
| SERVICE U-VALUE | W/(m ² .°C) | 6 734,01 | |
| LMTD | °C | 5,00 | |
| PLATE THICKNESS / MATERIAL | | 0.40 mm AISI 316L | |
| GASKET MATERIAL / TYPE | | EPDM HT | |
| DESIGN TEMPERATURE | °C | 120,00 | |
| WORKING PRESSURE | bar | 10,00 | |
| TEST PRESSURE | bar | 13,00 | |
| DESIGN CODE | | PED 97/32/EC | |
| LIQUID VOLUME | L | 34,23 | |
| MAX. NUMBER OF PLATES | | 150 | |
| NET WEIGHT | kg | 198,86 | |
| FLOODED WEIGHT | kg | 233,09 | |
| CONNECTION HOT | | DN50 Threaded BSP AISI 316 | |
| CONNECTION COLD | | DN50 Threaded BSP AISI 316 | |